

## Pro XD Full-Size Gas Crew



### Key Specifications

<b>Gas</b>	<b>2,000</b>	<b>200-Hr</b>
<b>Fuel Type</b>	<b>lbs Payload</b>	<b>Maintenance Interval</b>

#### ANSI/OPEI Certification

Polaris Industries Inc. certifies that these vehicles complies with the American National Standard for Multipurpose off-Highway Utility Vehicles, ANSI/OPEI B71.9 – 2016 Standard

## Engine & Drivetrain

<b>Air Intake</b>	Front Air Intake with Donaldson® Cyclonic Air Filter
<b>Cooling</b>	Liquid
<b>Cylinders Displacement</b>	1,000 cc
<b>Drive System Type</b>	On-Demand 4x4
<b>Engine Type</b>	ProStar 1,000 cc Gas
<b>Fuel System/Battery</b>	Electronic Fuel Injection
<b>Horsepower</b>	39.5 HP
<b>Maintenance Interval</b>	200 Hours (50 Hour initial)
<b>Top Speed</b>	Adjustable up to 40 mph (64 km/h)
<b>Transmission/Final Drive</b>	Automatic PVT H/L/N/R/P; Shaft

## Dimensions

<b>Bed Box Dimensions (L x W x H)</b>	43.5 x 54 x 11.5 in (110.5 x 137 x 29 cm)
<b>Box Capacity</b>	1,250 lb (567 kg)
<b>Estimated Dry Weight</b>	1,864 lb (845 kg)
<b>Fuel Capacity</b>	11.5 gal (43.5 L)
<b>Ground Clearance</b>	11 in (27.9 cm)
<b>GVWR</b>	4,000 lb (1,814 kg)
<b>Hitch Towing Rating</b>	2,500 lb (1,134 kg)
<b>Overall Vehicle Size (L x W x H)</b>	157 x 62.5 x 75 in (399 x 159 x 191 cm)
<b>Payload Capacity</b>	2,000 lb (907 kg)

<b>Person Capacity</b>	4
<b>Turning Radius</b>	207 in (525 cm)
<b>Wheelbase</b>	117 in (297.2 cm)

## Brakes

<b>Front/Rear Brakes</b>	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
<b>Parking Brake</b>	Park In-Transmission

## Additional Specifications

<b>Adjustable Driver Seat</b>	Not Equipped
<b>Cargo System</b>	Lock & Ride®
<b>Hitch Type</b>	Standard 2 in (5 cm) Receiver
<b>Instrumentation</b>	All Digital Gauge, Speedometer, Odometer, Tachometer, 2 Tripmeters, Hour Meter, Gear Indicator, Diff Lock Indicator, High-Temp Light, Clock, Clutch Belt Slip Warning, Low Oil Pressure Indicator, Seat Belt Indicator
<b>Lighting</b>	55W low/ 60W high, LED Tail
<b>Other Standard Features</b>	Horn, Backup Alarm, Password protected, electronically adjustable speed limiting
<b>Seat Covering</b>	Kevlar®-Backed Vinyl (Grey)
<b>Tilt Steering</b>	Standard

## Tires / Wheels

<b>Electronic Power Steering</b>	Standard
<b>Front Tires</b>	26 x 10-12 Duro® DI-2042 Power Grip (M/T)
<b>Hubs</b>	Front: Steel; Rear: Ductile Iron
<b>Rear Tires</b>	26 x 10-12 Duro® DI-2042 Power Grip (M/T)
<b>Wheels</b>	12 x 6 HD Steel - Gloss Black

## Suspension

<b>Front Suspension</b>	9 in (22.9 cm)
<b>Rear Suspension</b>	9 in (22.9 cm)